

# List of Tables

<b>Table 2.1:</b> The decibel. Approximated relationships for power and amplitude	<b>23</b>
<b>Table 2.2:</b> Gain and Phase	<b>33</b>
<b>Table 2.3:</b> Some points of the $y_1$ and $y_2$ curves (Fig. 2.15b)	<b>36</b>
<b>Table 3.1:</b> Levels in a 3-bit resolution converter	<b>69</b>
<b>Table 3.2:</b> Representation of the signal of Figure 3.15 in decimal and binary codes	<b>69</b>
<b>Table 3.3:</b> Amount of bits and number of levels	<b>70</b>
<b>Table 3.4:</b> Bytes, bits and levels	<b>70</b>
<b>Table 4.1:</b> Gains and standard resistors $R_6$	<b>107</b>
<b>Table 4.2:</b> Characteristics of temperature sensors	<b>131</b>
<b>Table 4.3:</b> Cell constants and measuring ranges	<b>142</b>
<b>Table 4.4:</b> Piezoelectric transducers in air	<b>157</b>
<b>Table 4.5:</b> Synopsis of sensors	<b>167</b>
<b>Table 5.1:</b> Error for an EMFM	<b>176</b>
<b>Table 5.2:</b> Units of heat transfer equations	<b>197</b>
<b>Table 6.1:</b> Direct methods characteristics	<b>239</b>
<b>Table 8.1:</b> DTS specifications of commercial equipment	<b>281</b>
<b>Table 8.2:</b> Some Characteristics of two SODAR systems	<b>292</b>
<b>Table 8.3:</b> The relation between pulse duration and length and spatial resolution	<b>306</b>
<b>Table 8.4:</b> Examples of pulse repetition rate ( $prr$ )	<b>306</b>
<b>Table 8.5:</b> A commercial lidar for wind farm evaluations	<b>308</b>
<b>Table 8.6:</b> Another lidar, but for larger range applications	<b>308</b>
<b>Table 9.1:</b> Lengths and speeds for some serial connections	<b>340</b>
<b>Table 10.1:</b> Microwave bands	<b>382</b>
<b>Table 11.1:</b> Steps for a field measuring campaign	<b>402</b>
<b>Table 11.2:</b> Real change in depth versus measured change	<b>413</b>
<b>Table 11.3:</b> Real change in depth versus measured change	<b>413</b>